

TECHNICAL SPECIFICATIONS		
Model	eIQ-18WMINVB	
Rated volt and frequency	1-220-240/50	
Mode	Cooling	Heating
Rated capacity (W)	5100 (1800~5900)	5200 (1800~6100)
Cooling power input (W)	1600 (420~2100)	1400 (410~2150)
Heating current input (A)	7.2 (1.9~9.5)	6.4 (1.8~9.7)
SEER/SCOP(W/W)	6.1/ A++	4.0/ A+
Nominal load (kW)	5.1	4.5
Balance point temperatureheating (°C)	/	-7
Min.outdoor operating temperature (°C)	/	-10
Thermostat-off mode (W)	60	
Standby mode (W)	0.5	
Off mode (W)	0	
Annual consumption (KW)	381	1925
Copper Pipe Type length	5m	
Liquid side/Gas side (mm/inch)	6.00(1/4)+12(1/2)	
Max.refrigerant pipe length	15m	
Max.elevation	5m	
Interconnecting Cable	3C+E	
Fuse Rating	24A	
Moisture Removal (L/h)	2.23	
INDOOR UNIT	Air Flow (m3/h)	850
	Dimension (L*W*H) (mm)	900*292*215
	Packaging (L*W*H) (mm)	983*377*300
	Net/Gross weight (Kg)	14/17
	Noise - Sound pressure level (dB/A)	42~46
	Noise - Sound power level (dB/A)	52~56
OUTDOOR UNIT	Dimension (L*W*H) (mm)	850*295*605
	Packaging (L*W*H) (mm)	995*415*690
	Net/Gross weight (Kg)	40/45
	Noise - Sound pressure level (dB/A)	55
	Noise - Sound power level (dB/A)	65

	Refrigerant type/weight	R410A/1350g
	Defrost mode	Automatic