

## TECHNICAL SPECIFICATIONS

Model		eIQ-24WMINVB	
Rated volt and frequency		1-220-240/50	
Mode		Cooling	Heating
Rated capacity (W)		6100 (2500~ 6500)	6100 (2100~ 7000)
Cooling power input (W)		1900 (700~3000)	1680 (450~2300)
Heating current input (A)		8.3 (3.2~ 13.6)	7.4 (2.6~ 10.5)
SEER/SCOP(W/W)		5.6/ A+	4.0/ A+
Nominal load (kW)		6.1	5.5
Balance point temperatureheating (°C)		/	-7
Min.outdoor operating temperature (°C)		/	-10
Thermostat-off mode (W)		70	
Standby mode (W)		0.5	
Off mode (W)		0	
Annual consumption (KW)		381	1925
Copper Pipe Type length		5m	
Liquid side/Gas side (mm/inch)		6.00(1/4)+12(1/2)	
Max.refrigerant pipe length		15m	
Max.elevation		5m	
Interconnecting Cable		3C+E	
Fuse Rating		24A	
Moisture Removal (L/h)		2.23	
INDOOR UNIT	Air Flow (m3/h)	1050	
	Dimension (L*W*H) (mm)	1080x302x220	
	Packaging (L*W*H) (mm)	1275x392x318	
	Net/Gross weight (Kg)	16/20	
	Noise - Sound pressure level (dB/A)	42~48	
	Noise - Sound power level (dB/A)	52~58	
OUTDOOR UNIT	Dimension (L*W*H) (mm)	850x295x605	
	Packaging (L*W*H) (mm)	995x415x690	
	Net/Gross weight (Kg)	45/51	
	Noise - Sound pressure level (dB/A)	55	
	Noise - Sound power level (dB/A)	65	

	Refrigerant type/weight	R410A/1920g
	Defrost mode	Automatic