

Model		eiQ-SSRFC48K-V4		eiQ-SSRFC60K-V4	
Indoor Rated voltage and frequency (Ph-V-Hz)		N/A		N/A	
Outdoor Rated voltage and frequency (Ph-V-Hz)		380~415/3/50		380~415/3/50	
Indoor Fuse Required		N/A		N/A	
Outdoor Fuse Required		20A		20A	
Mode		Cooling	Heating	Cooling	Heating
Rated capacity (KW)		14.0 (7.0-15.5)	15.2 (8.0-16.0)	16.0(7.5-17.0)	16.8 (8.5-17.5)
Power input (W)		4950 (1100-5800)	4920 (1200-6000)	5900 (1400-6300)	5460 (1500-6500)
Current input (A)		2.8-14.6	3.0-15.0	3.5-15.8	3.7-16.3
SEER/SCOP(W/W)		6.1 / A++	4.0 / A+	6.1 / A++	4.0 / A+
Nominal load (kW)		14.000	11.500	16.000	12.000
Balance point temperature heating (°C)		-	-7	-	-7
Min. outdoor operating temperature (°C)		-15	-15	-15	-15
Thermostat-off mode (W)		101	23.9	128	23.6
Standby mode (W)		3		3	
Off mode (W)		3		3	
Annual consumption (kW)		795	3723	911	4046
Copper Pipe Type length		-		-	
Liquid side / Gas side (mm/inch)		Φ9.52/Φ15.88		Φ9.52/Φ15.88	
Max. refrigerant pipe length		65		65	
Max. elevation		30		30	
Interconnecting Cable		4 x 2.5mm ²		4 x 2.5mm ²	
Moisture Removal (L/h)		5.08		7.96	
Indoor	Air Flow (m ³ /h)	1900		2000	
	Body Dimensions (L*W*H) (mm)	840x285x840		840x285x840	
	Panel Dimensions (L*W*H) (mm)	950x50x950		950x50x950	
	Body Packaging (L*W*H) (mm)	920x310x920		920x310x920	
	Panel Packaging (L*W*H) (mm)	1030x100x1030		1030x100x1030	
	Body Net / Gross weight (Kg)	29/34		29/34	
	Panel Net / Gross weight (Kg)	6.5/9.5		6.5/9.5	
	Noise – Sound pressure level (dB/A)	45-52		45-52	
	Noise – Sound power level (dB/A)	56-63		56-63	
Outdoor	Dimension (L*W*H) (mm)	1014x1430x450		1014x1430x450	
	Packaging (L*W*H) (mm)	1095x485x1545		1095x485x1545	
	Net / Gross Weight (Kg)	109/123.6		112/126.6	
	Noise – Sound pressure level (dB/A)	58		58	
	Noise – Sound power level (dB/A)	70		70	
	Refrigerant type/weight	R32 / 3800g		R32 / 3800g	
	Defrost mode	Automatic defrosting		Automatic defrosting	
	Applicable climate types	Cooling (-15°C – 50°C) Heating(-15°C – 30°C)		Cooling (-15°C – 50°C) Heating(-15°C – 30°C)	

Due to continuous product development process specification may change.

These units contain a gas governed by F-Gas regulations. The gas must be handled by qualified F-Gas engineers.